



PRODUCT SPECIFICATION

IMC 312 - LOW-OXYGEN COPPER



Copper ⁽¹⁾	99.95 MIN%
Iron	0.003 MAX%
Sulfur	0.003 MAX%
Lead	0.002 MAX%
Antimony	0.002 MAX%
Nickel	0.002 MAX%
Arsenic	0.001 MAX%
Tin	0.002 MAX%
Total Other ⁽²⁾	0.010 MAX%
Oxygen	0.0035 MAX%

(1) Copper includes Silver

(2) Other metallic elements include: Bi, Cd, Mn, Hg, Se, Te, Zn

SIZES

LOW-OXYGEN COPPER BARS

OVALS

1.75" x 3" / 45mm x 75mm

RECTANGLES

1" x 4" / 25mm x 100mm

DRILL AND TAP (D&T)

STD - 3/8-16 x 1"

Custom D&T Available

PACKAGING

• Boxed, Palletized

• Pallet weight varies based on anode length

FEATURES

- Hot rolling produces a fine-grained structure.
- Consistent dissolution.
- Special process eliminates precleaning.
- For use with anode hooks or trays.
- Certificate of Analysis issued for every lot.

TYPICAL APPLICATIONS

- Decorative Plating
- Electronic Components
- Corrosion Protection in Automotive Parts
- Electrical Connectors
- Power Distribution Equipment
- Ammunition
- Coinage
- Wire Plating

CAS NUMBER: 7440 – 50-8 / MSDS NUMBER: 2007

This information herein is believed to be reliable, however, no warranty, expressed or implied, is made as to its accuracy or completeness and none is made as to the fitness of this material for any purpose. The manufacturer shall not be liable to damages to person or property resulting from its use. Nothing herein shall be construed as a recommendation for use in violation of any patents.

135 Old Boiling Springs Road • Shelby, NC 28152